


AVIGILON™

16 I/O Elevator Board

Expandable access control for the modern workplace



The Avigilon 16 I/O Elevator Board extends access control capabilities to standard elevators, enabling security operations to secure and control access to specific floors. Each Elevator Board can support up to 16 floors and two Avigilon Smart Readers, making it easy to bring robust security and frictionless access to elevators.



Simplified install

Easy to install, using industry standard RS-485 signaling to communicate with Smart Readers over standard wiring, and USB to connect to the Access Control Core. The Expansion Board features removable contact terminal blocks for easier wiring.



Multiple elevator support

Easily supports up to 16 floors, which can be split between multiple elevators, with port interfaces for 2 Avigilon Smart Readers, 16 relays, and 16 general-purpose inputs.



On-board indicators

Elevator Boards feature multiple LEDs to provide easy visibility of connectivity and configuration status.



Easy management and monitoring

Cloud management provides secure, remote access and eliminates the need to set up or maintain local servers. Get real-time visibility and insights to elevator access events from anywhere.



Scalable design

Each Access Control Core can support up to two Elevator Boards to support additional floors and elevators.



Lifetime limited warranty

Ensure peace of mind, knowing that Avigilon stands behind its access control hardware with a lifetime limited warranty, guaranteeing the quality of your security solution.

Specifications

CAPACITY

Elevator Floors Up to 16 floors

INTERFACES

Reader Ports 2 RS-485 ports for 2 Avigilon Smart Readers

Relay Ports 16 dry relay ports (1A/24VDC or 0.5A/125VDC Contact)

Input Ports 16 input ports (Nominal 3V-24VDC)

USB Ports 1 USB port to communicate with the Access Control Core


GENERAL

LED Indicators Board power on or off, board ID number, connection status to Access Control Core

Power 325mA @ 12VDC
Exclude operating current for attached readers
190mA @ 24VDC

DIMENSIONS

Device Only



Weight 0.875 lbs (397 g)

ENVIRONMENTAL

Temperature Operating Temperature: 0°C (32°F) to 50°C (122°F)

Humidity Operating Humidity: 5% to 85% relative, non-condensing

REGULATORY

Certifications FCC (United States), IC (Canada), CE (Europe), UL 294

WARRANTY

Avigilon Alta Access Warranty Lifetime limited; for more information, visit avigilon.com/support/warranty



Ordering Information

PART NUMBER	DESCRIPTION
OP-16EM	Avigilon16 I/O Elevator Board

Support

For product support, visit: [avigilon.com](https://www.avigilon.com) or sales@avigilon.com

For more information, visit:
[avigilon.com/access-control/elevator-board](https://www.avigilon.com/access-control/elevator-board)



AVIGILON

Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. [motorolasolutions.com](https://www.motorolasolutions.com)

© 2024, Avigilon Corporation. All rights reserved. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners.

20240719-en